



eXtreme pine

products for life

Strong, durable and sustainable timber products
manufactured to withstand the test of time

eXtreme pine

eXtreme pine is part of the eXtreme Timber range of engineered timber products with excellent durability and exceptional strength, plus added exterior preservation systems to create a product you can trust.

Using radiata pine, one of the most versatile building products currently available, eXtreme Timber has all large defects removed to ensure maximum structural performance as well as aesthetic beauty for any setting.

Size and stability is enhanced by the use of finger jointing and lamination technology in all products. The adhesive systems selected are all service class 3 for external in or above ground applications. This adhesive system has excellent bond strength and for many years has been used in a range of exposed applications including timber boat manufacture.

This adhesive system is combined with time proven timber preservation systems that are impregnated into the plantation grown FSC® certified timber, creating a long lasting, sustainable product with great durability and performance.



PINE



Large, long and straight posts for any application with the added benefit of being able to be put in the ground. eXtreme Posts can do it for you.

Sizes	Strength	Finish	Hazard class	Available lengths
88 x 88mm	GL8	RH or Dressed smooth	H4	2.4, 2.7, 3.0, 3.6, 4.2, 4.8, 5.4, 6.0m
112 x 112mm	GL8	Dressed smooth	H4	2.4, 2.7, 3.0, 3.6, 4.2, 4.8, 5.4, 6.0m
135 x 135mm	GL8	Dressed smooth	H4	2.4, 2.7, 3.0, 3.6, 4.2, 4.8, 5.4, 6.0m



SPAN TABLES AVAILABLE ONLINE
DOWNLOAD TODAY



PINE



Long spans for beams and rafters with the option of either stain, paint or hide in a wall. eXtreme Beam has a vast array of sizes and lengths to allow for endless design options.

Sizes	Strength	Finish	Hazard class	Available lengths
90 x 70mm	GL8	Rougher headed	H4	3.6, 4.2, 4.8, 5.4, 6.0m
140 x 65mm	GL8	Rougher headed	H3	3.6, 4.2, 4.8, 5.4, 6.0m
180 x 65mm	GL8	Rougher headed	H3	3.6, 4.2, 4.8, 5.4, 6.0m
240 x 65mm	GL8	Rougher headed	H3	3.6, 4.2, 4.8, 5.4, 6.0m
290 x 65mm	GL8	Rougher headed	H3	3.6, 4.2, 4.8, 5.4, 6.0m