



Would your decking meet BAL-40? ModWood Flame Shield® Would!



- Decking with a traditional look and feel with a bushfire attack level rating of BAL-40.
- Is certified for use BAL-12.5, BAL-19, BAL-29 and BAL-40!
- Deep embossed pattern improves slip resistance, manufactured to R11
- Durability with low maintenance
- Australian designed, manufactured and tested



Bushfires are part of Australia's environment and enjoying the use of a deck is a central part of the Australian lifestyle. Until now, the options available for decking boards suited to bushfire prone areas rated at BAL-40 have been very limited. However, this has all changed!

Flame Shield® can be used in bushfire prone areas that have bushfire attack levels of BAL-40, BAL-29, BAL-19 and BAL-12.5 (AS3959-2009). **Flame Shield®** is certified to AS1530.8.1-2007 and is available in a 137mm x 23mm profile from the ModWood Natural Grain Collection range of colours.



Flame Shield® certification allows for the subfloor space to be either enclosed* or unenclosed. The sub-frame joists and bearers need to be from non-combustible materials or one of the bushfire-resisting timbers (refer to AS3959-2009 Appendix F). With this construction system, **Flame Shield®** has been tested and certified to comply with AS1530.8.1.

Flame Shield® is manufactured with a deep embossed pattern for improved slip resistance and achieves R11 (AS/NZS 4586-2004).

ModWood **Flame Shield®** boards are designed and manufactured in Australia to meet local conditions. **Flame Shield®** is specially formulated wood composite decking that has a rating of BAL-40. Choose and use with confidence, knowing that **Flame Shield®** has been designed for the harsh Australian environment.



Flame Shield® is a registered trade mark of ModWood Technologies Pty Ltd.
Further information can be obtained by visiting www.modwood.com.au

* Please refer to ModWood ventilation requirements.